



# FREEWAY ISUZU TRUCK

Mark Lund | 6027376150 | mark@freewayisuzutruck.com

## City of Menifee/MVcupboard



Current report content is based on data as of 2023-03-15 11:17:48. Any performance-related calculations are offered solely as guidelines. Actual vehicle performance will depend on your operating conditions. All Information, specifications and pricing in this application are based on the latest information available. Isuzu Commercial Truck of America, Inc. reserves the right to discontinue or change, at any time, without prior notice, the pricing, specifications, options, materials, equipment, design and models.



# FREEWAY ISUZU TRUCK

Mark Lund | 6027376150 | mark@freewayisuzutruck.com

City of Menifee/MVcupboard #JALE5W169P7301346 (2023 NRR Cab Chassis, 3U3 150"WB, 127.5"CA, 19,500 GVWR. White, 30 Gallon Stainless Steel In-Rail Fuel Tank with power windows, power door locks and air conditioning

## Selected Model and Options

	Code	Description	Weight	MSRP
<b>Model</b>				
	3U3	NRR Cab Chassis 150"WB, 127.5"CA		\$66,100.00
	54	White, 30 Gallon Stainless Steel In-Rail Fuel Tank with power windows, power door locks and air conditioning		\$0.00
<b>Tires</b>				
	I5H	LRR (low rolling resistance)	0.0 lbs.	Inc.
<b>Engine</b>				
	I1B	4HK1-TC, diesel engine 317 CID (5.19L), 215 HP at 2550 RPM: 452 ft.-lb. gross torque at 1850 RPM. 4 cylinder, 16 valve, four cycle, overhead cam, turbocharged, inter-cooled, water cooled EGR valve, direct injection, electronically controlled common rail fuel system, engine cruise control function. Oil level check switch and light. Engine Warning system with audible warning for low oil pressure, high coolant temperature, and low coolant level.	0.0 lbs.	Inc.
<b>Transmission</b>				
	I1W	Aisin A465id 6-speed automatic transmission, Ratios: 3.742, 2.003, 1.343,	0.0 lbs.	Inc.
<b>Wheelbase</b>				
	IB1	150 inches, includes ladder type channel frame. Full C section straight frame 33.5 inches wide. Yield strength 44,000 psi; section modulus 7.20in3 RBM 316,800 lb./ft./in. per rail. 127.5"CA	0.0 lbs.	Inc.
<b>Air Cleaner</b>				
	KNX	Dry Paper single element. (Donaldson brand) Air cleaner canister standard with air restriction indicator in the driver's Multi-Information Display (MID).	0.0 lbs.	Inc.
<b>Alternator</b>				
	I2C	140 AMP. with integral regulator.	0.0 lbs.	Inc.
<b>Battery</b>				
	IX1	Dual 12-Volt maintenance free group 31 750 CCA batteries with threaded posts	0.0 lbs.	Inc.
<b>Exhaust</b>				
	IX7	Single horizontal with DPF/SCR exhaust system	0.0 lbs.	Inc.
<b>Front Axle</b>				
	I26	"I"-beam rated at 7,275 lbs. Includes integral hydraulic power steering. Ratio 18.8-20.9:1.	0.0 lbs.	Inc.
<b>Front Suspension</b>				
	ID8	8440 lbs. Capacity semi elliptical tapered leaf spring. Includes shock absorbers and stabilizer bar	0.0 lbs.	Inc.
<b>Front Wheels</b>				
	IB9	19.5" x 6", 6-hole disc, painted white	0.0 lbs.	Inc.
<b>Front Tires</b>				
	XTN/R3M	225/70R19.5F (12 ply) tubeless Radial, all season	0.0 lbs.	Inc.
<b>Rear Suspension</b>				
	ID9	14,550 lbs. capacity. Semi-elliptical main and	0.0 lbs.	Inc.

Current report content is based on data as of 2023-03-15 11:17:48. Any performance-related calculations are offered solely as guidelines. Actual vehicle performance will depend on your operating conditions. All Information, specifications and pricing in this application are based on the latest information available. Isuzu Commercial Truck of America, Inc. reserves the right to discontinue or change, at any time, without prior notice, the pricing, specifications, options, materials, equipment, design and models.



# FREEWAY ISUZU TRUCK

Mark Lund | 6027376150 | mark@freewayisuzutruck.com

City of Menifee/MVcupboard #JALE5W169P7301346 (2023 NRR Cab Chassis, 3U3 150"WB, 127.5"CA, 19,500 GVWR. White, 30 Gallon Stainless Steel In-Rail Fuel Tank with power windows, power door locks and air conditioning

## Selected Model and Options

Code	Description	Weight	MSRP
	auxiliary multi-leaf springs. Includes shock absorbers.		
Rear Axle			
ID3	Single-speed, 14,550 lb. capacity with oil lubricated rear wheel bearings.	0.0 lbs.	Inc.
Ratio			
011	5.571:1	0.0 lbs.	Inc.
Rear Wheels			
IC1	19.5" x 6", 6-hole disc, painted white	0.0 lbs.	Inc.
Rear Tires			
YTN/S3M	225/70R19.5F (12 ply) tubeless Radial, all season tread.	0.0 lbs.	Inc.
Fuel Tank			
I4I	30 Gallon Stainless Steel In-Rail Fuel Tank	0.0 lbs.	Inc.
Seat			
AQB	Driver seat is reclining high back. Two single occupant fold down seats with tray backs.	0.0 lbs.	Inc.
Brakes			
K40	Butterfly valve type exhaust brake	0.0 lbs.	Inc.
IE1	Vacuum + Power Assist; hydraulic 4-wheel disc brakes with 4-channel ABS. Mechanical, transmission mounted parking brake. Non-asbestos semi metallic linings are standard.	0.0 lbs.	Inc.
Air Conditioning			
C60	Air conditioner	0.0 lbs.	Inc.
Power Windows & Door Locks			
IL0	Yes	0.0 lbs.	Inc.
Floor Mats			
IQ6	Standard Floor Mats	0.0 lbs.	Inc.
Model Option			
54	White, 30 Gallon Stainless Steel In-Rail Fuel Tank with power windows, power door locks and air conditioning	0.0 lbs.	Inc.
Additional Options			
IF6	Fire Extinguisher and Triangle Kit mounted in rear organizer on standard cab and under rear seat on crew cab	19.0 lbs.	\$88.00
IV8	Seat Covers standard cab	6.0 lbs.	\$280.00
UZF	Back up alarm	1.0 lbs.	\$112.00
I4K	Keyless entry system including two keypads as standard	1.0 lbs.	\$316.00
I6K	Lockable DEF fill cap	0.3 lbs.	\$80.00
I8L	High visibility seat belt (driver and RH passenger seat)	0.0 lbs.	\$184.00
I0W	Heated dual remote control mirrors (17" head)	4.0 lbs.	\$676.00
I3Z	Spare keys (2 additional, 4 keys in total)	0.0 lbs.	\$40.00
Assistance System			

Current report content is based on data as of 2023-03-15 11:17:48. Any performance-related calculations are offered solely as guidelines. Actual vehicle performance will depend on your operating conditions. All Information, specifications and pricing in this application are based on the latest information available. Isuzu Commercial Truck of America, Inc. reserves the right to discontinue or change, at any time, without prior notice, the pricing, specifications, options, materials, equipment, design and models.



# FREEWAY ISUZU TRUCK

Mark Lund | 6027376150 | mark@freewayisuzutruck.com

City of Menifee/MVcupboard #JALE5W169P7301346 (2023 NRR Cab Chassis, 3U3 150"WB, 127.5"CA, 19,500 GVWR. White, 30 Gallon Stainless Steel In-Rail Fuel Tank with power windows, power door locks and air conditioning

Selected Model and Options			
	Code	Description	MSRP
	I5I	Electronic Vehicle Stability Control (EVSC) include ASR (Anti-Slip Regulation)	Inc.
Accessories			
	IX2	Rear body dome lamp switch	Inc.
	8RP	AM/FM/CD radio with Aux input/USB port and Bluetooth RPO	Inc.
Totals			
		Base Price	\$66,100.00
		Destination Charge	\$1,825.00
		Material & Transportation Surcharge	\$2,475.00
		DEF Fill Charge	\$10.00
		Total Options Price	\$1,776.00
		Tire Weight Tax	\$7.94
		Total	\$72,193.94

Current report content is based on data as of 2023-03-15 11:17:48. Any performance-related calculations are offered solely as guidelines. Actual vehicle performance will depend on your operating conditions. All Information, specifications and pricing in this application are based on the latest information available. Isuzu Commercial Truck of America, Inc. reserves the right to discontinue or change, at any time, without prior notice, the pricing, specifications, options, materials, equipment, design and models.



# FREEWAY ISUZU TRUCK

Mark Lund | 6027376150 | mark@freewayisuzutruck.com

City of Menifee/MVcupboard #JALE5W169P7301346 (2023 NRR Cab Chassis, 3U3 150"WB, 127.5"CA, 19,500 GVWR. White, 30 Gallon Stainless Steel In-Rail Fuel Tank with power windows, power door locks and air conditioning

## Quote Worksheet

	MSRP
Base Price	\$66,100.00
Destination Charge	\$1,825.00
Material & Transportation Surcharge	\$2,475.00
DEF Fill Charge	\$10.00
Total Options	\$1,776.00
<b>Subtotal</b>	<b>\$72,186.00</b>
<b>Subtotal Additional Equipment</b>	<b>\$0.00</b>
16 foot insulated refrigerated Summit body with Thermo king reefer unit 520 with electric standby. 48 inch Maxon tuckunder liftgate	\$48,450.00
<b>Subtotal Miscellaneous Equipment</b>	<b>\$48,450.00</b>
<b>Pre-Tax Subtotal</b>	<b>\$120,636.00</b>
mkt surcharge	\$7,000.00
<b>Subtotal Discount</b>	<b>\$7,000.00</b>
<b>Taxable Price</b>	<b>\$127,636.00</b>
Sales Tax	8.75% \$11,168.15
Tire Weight Tax	\$7.94
<b>Subtotal Taxes</b>	<b>\$11,176.09</b>
New Item	\$0.00
estimated license	\$1,488.00
<b>Subtotal Post-Tax Adjustments</b>	<b>\$1,488.00</b>
Less Post-tax Customer Discount	\$0.00
<b>Subtotal Discount</b>	<b>\$0.00</b>
<b>Total Sales Price</b>	<b>\$140,300.09</b>

\_\_\_\_\_  
Dealer Signature/Date

\_\_\_\_\_  
Customer Signature/Date

Current report content is based on data as of 2023-03-15 11:17:48. Any performance-related calculations are offered solely as guidelines. Actual vehicle performance will depend on your operating conditions. All Information, specifications and pricing in this application are based on the latest information available. Isuzu Commercial Truck of America, Inc. reserves the right to discontinue or change, at any time, without prior notice, the pricing, specifications, options, materials, equipment, design and models.